




## Barometers



- ▶ Wide range of models with technical specifications for meteorological applications
- ▶ Analogue outputs (DQA240A.1, DQA801)
- ▶ RS485, Ethernet digital outputs (DQA251)
- ▶ Very good accuracy:  $\pm 0,15$  hPa (@20°C)  $\pm 0,20$  hPa (-40...60 °C) (DQA251)
- ▶ QNH, QFE, QFF measurements (DQA251+Alpha-Log)
- ▶ Alpha-Log data logger is equipped with internal pressure sensor. In the data sheet of the data logger, technical specifications of this sensor are described (Read Alpha-Log column)




Sensors designed for accurate measurement of atmospheric pressure. DQA240A.1 is more suitable for LSI LASTEM data acquisition systems (0...1V DC output). DQA801 is also suitable for integration in third party systems (0/4...20 mA output), its range is locally selectable by trimmer. DQA251 is a high precision instrument for absolute pressure, QNH, QFE, QFF. Long-term stability and a web interface make it the perfect instrument for professional acquisition systems, meteorology and aviation. Heavy duty enclosure IP67, allows an easy installation also in harsh environmental conditions. DQA251 sensor is built according WMO and ICAO standards.

### Technical Specifications

PN	DQA240A.1	DQA801	DQA251	Alpha-Log
				
<b>Output</b>	0...1 V	0/4...20 mA	Modbus on RS485; Modbus on TCP-IP, Lan-Ethernet; autosending on RS232 (ASCII file every 3"), FTP (SDI12 Optional)	Read Data-Logger spec.
<b>Measurement</b>	Absolute Pressure		Absolute Pressure QNH, QFE, QFF according to CIMO/ET-Standard-1/Doc.10 (20.XI.2012) WMO -2012	
<b>Number of transducers</b>	1		1 (optional 3)	1
<b>Memory</b>	NO		128 Mb (about 3 years measurements)	Read Data-Logger spec.
<b>Data display</b>	NO		<ul style="list-style-type: none"> <li>• by built-in LCD 2x24 chr display</li> <li>• by web-browser on a connected PC (charts and numeric values)</li> </ul>	Read Data-Logger spec.
<b>Data download</b>	NO		Last 30 days measurements in Excel and ASCII files by Ethernet port	Read Data-Logger spec.

PN	DQA240A.1	DQA801	DQA251	Alpha-Log
<b>Power supply</b>	10...14 V DC	10...30 V DC/AC	10.8-15 V DC	Read Data-Logger spec.
<b>Power consumption</b>	0.25 W	0.5 W	<0.6 W (~45mA @ 12 V DC)	Read Data-Logger spec.
<b>Accuracy</b>	±0.5 hPa		±0.15 hPa (@20 °C) ±0,20 hPa (-40...60 °C)	±1 hPa
<b>Thermal drift</b>	Compensated into the range: 10...60 °C. Drift in the range-20...10 °C: -0,025 hPa/°C		Compensated into the range: -40...60°C	Compensated into the range: -20...85 °C
<b>Range</b>	800...1100 hPa	Default: 800...1100 hPa (selectable 600...1100 hPa, 700...1100 hPa)	500...1200 hPa	500...1100 hPa
<b>Linearity</b>	NA	NA	±0.1hPa / <0.05hPa	NA
<b>Resolution</b>	0.1 hPa		0.01 hPa	0.084 hPa
<b>Response time</b>	0.5 s		0.1 s	0.1 s
<b>Long term stability</b>	<±0.5 hPa/year		<±0.1 hPa/year	
<b>Calibration</b>	Data Logger setup	By trimmer	By internal software	
<b>Calibration certificate</b>	Not included		Included	Not included
<b>Maximum pressure limit</b>	2000 hPa		3000 hPa	
<b>Principle</b>	Piezoresistor			
<b>Protection</b>	IP43	IP65	IP67	IP43
<b>Weight</b>	0.2 kg	0.3 kg	1 kg	Read Data-Logger spec.
<b>Installation</b>	Inside ELFxxx enclosures	On DYA078 bracket	On DIN bar	Read Data-Logger spec.
<b>Cable</b>	Included, L=20 cm	See Accessories	Included	-
<b>Operative temperature</b>	-40...85 °C		-30...80 °C	-40...80 °C
<b>Data logger compatibility</b>	E-Log Alpha-Log		Alpha-Log Using RS232->485 converter: E-Log	NA

**Accessories**

	<b>DWA505A</b>	Cable L=5 m for DQA801
	<b>DWA510A</b>	Cable L=10 m for DQA801
	<b>DWA525A</b>	Cable L=25 m for DQA801
	<b>DWA526A</b>	Cable L=50 m for DQA801
	<b>DWA527A</b>	Cable L=100 m for DQA801
	<b>MG2251.R</b>	7 pin free female connector
	<b>DYA078</b>	Support for DQA801 with radiant shield.
	<b>SVICA5001</b>	Calibration certificate/ISO9001 type (Absolute pressure)
	<b>SVACA5006.1</b>	Calibration certificate/ISO17025 type/N.6 points (Absolute pressure)