

## Net radiometer



- ▶ Sensor for measuring the radiant heat flow between two opposite faces of a flat element
- ▶ Integrated temperature sensor used to obtain the Planar Radiant Asymmetry
- ▶ When connected to M-Log, it is possible to obtain a range of parameters related to the radiant asymmetry and local discomfort index as described in the ISO7726 and ISO7730 standards
- ▶ Measurement of the Planar Radiant Asymmetry on three axes of the space
- ▶ Fast response time

Probe to measure the net radiation in confined environments. In environments with low air velocity it is possible to obtain a measurement close to the mean plane radiant temperature obtaining the direction of the radiant flow. To operate, the probe must be combined with a temperature probe. Portable use or attached to stands BVA305-315. Sensitivity value are reported in the calibration certificate enclosed.

### Technical Specifications

PN	PRRDA0110	
<b>Thermal flow between two semi-areas of the environment</b>  <b>General Information</b>	Principle	Termopile
	Spectral range	0.3...50 $\mu\text{m}$
	Accuracy	5% (Net radiation)
	Output	$\mu\text{V}/\text{W}/\text{m}^2$
	Range	-1500...1500 $\text{W}/\text{m}^2$
	Housing	Anodised aluminium
	Protection	IP54
	Operative temperature	-30...70 $^{\circ}\text{C}$
	Cable	L=1 m
	Connector	Double mini-DIN
	M-Log derived quantities obtained	Planar radiant asymmetry (ISO7726) Planar radiant mean temperature (ISO7726) People dissatisfied by radiant asymmetry (ISO7730)
	Mounting	On BVA320-315 stands
	Data logger compatibility	M-Log (ELO009)

### Accessories

	<b>DPA295</b>	Spare part: salts for PRRDA0110
--	---------------	---------------------------------

## Heat flow meter



- ▶ Used for heat flux measurement in the soil as well as through walls and building envelopes
- ▶ LSI LASTEM supplies a turn-key system to calculate the "U Factor" of the walls using heat flux and surface temperature sensors, data logger and software as described by the ISO 9869:1994 standard
- ▶ Suitable for long term and portable applications
- ▶ Sensor with free wire cable version (DPE240.x); sensor with cable and Mini-DIN connector (ESR240.x)

Sensor for heat flux measurement in the soil as well as through walls and building envelopes. It measures the heat that flows through the sensor and its surrounding environment. Heat may be exchanged through conduction with the solid, or by radiation and convection. Sensor sensitivity is reported in the calibration certificate. Thermo-conductive paste can be used to increase the heat exchange.

### Technical Specifications

PN	DPE240	DPE240A.1	ESR240	ESR240A.1	ESR240A.2
<b>Connector</b>	Free wires (4 wires)		Mini-Din connector		
<b>Cable</b>	5 m	15 m	5 m	10 m	25 m
<b>Data logger compatibility</b>	E-Log Alpha-Log (using ALIEM module)		M-Log (ELO009)		

### Common Technical Specifications

<b>Thermal flow on the wall or inside ground</b>	Principle	Termopile
	Uncertainty	5% over 12 h measurement
	Sensitivity/output	60 $\mu\text{V}/\text{W}/\text{m}^2$
	Range	-2000...2000 $\text{W}/\text{m}^2$
	Guard width to thickness ratio	5 m/m (as required by ISO 9869 D.3.1 standard)
	Sensor thermal resistance	$71 \times 10^{-4} \text{ K}/(\text{W}/\text{m}^2)$
<b>General Information</b>	Housing	Anodised aluminium
	Protection	IP67
	Weight	0.5 kg (with 5 m cable)
	Operative temperature	-30...70 °C
	Mounting	Fixed on a wall or buried in soil (thermo-conductive paste not included)

### Accessories

	<b>MM7500.R</b>	Thermo-conductive paste for surface application
	<b>SVICA4603</b>	ISO9001 type calibration certificate (Thermal flow)

LSI LASTEM Srl  
Via Ex SP. 161 Dosso, 9  
20049 Settala (MI)  
Italy

Tel. +39 02 954141  
Fax +39 02 95770594  
Email [info@lsi-lastem.com](mailto:info@lsi-lastem.com)  
[www.lsi-lastem.com](http://www.lsi-lastem.com)

